### **CITIZEN**

# The contemporary high-resolution label printer

Outstanding prints at 300 dpi



### Stylish, fast and compact

The CL-E331's compact, modern, functional design takes up very little desk space, is easy to use and is also perfectly at home in any location, from warehouses to hospitals. It also has a fast print speed of 6 inches-per-second, is quick to setup and to load with media.

#### Well connected

The CL-E331 features on-board LAN, USB and Serial interfaces. All industry-standard emulations are fully supported, with the option of remote operation via a web browser, using the Citizen LinkServer™ management tool.

#### High quality printing in 300dpi

The CL-E331 the ideal choice for applications ranging from small test tube labels in healthcare to detailed rating plates in manufacturing. It is also equally suited to printing EAN barcodes and asset labels in the retail sector.

### **CL-E331**

### Label, Desktop

### **Applications**

- Manufacturing
- Healthcare
- Pharmacy
- Retail



Prints at a resolution of 300 dpi for when a clearer more detailed output is needed.

TOMORROW'S PRINTING TODAY

### **CITIZEN**



Ethernet LAN, USB and Serial interfaces as standard

### **Specifications**

Model	CL-E331
Printing Technology	Thermal Transfer + Direct Thermal
Resolution	300 dpi
Print Speed (maximum)	6 inches per second (150 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	1 - 4.6 inches (25 - 118 mm)
Roll Size (max), Core Size	Inside diameter 5 inches (125 mm) Core size 1 inch (25mm)
Media Thickness (min to max)	63.5 to 190 μm
Media Length (min to max)	0.25 to 64 inches (6.35 to 1625.6 mm)
Media Sensor	Fully adjustable gap, notch and reflective black mark
Main Interface	Triple interface USB 2.0, RS-232 and 10/100 Ethernet
Ribbon size	2.6 inches (60 mm) maximum outside diameter. 300 metres length. 1 inch (25 mm core)
Ribbon winding & type	Ink side out. Wax, Wax/Resin or Resin Type
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Emulations (Languages)	Datamax® DMX, Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations, Zebra® ZPL2® , CBI™ BASIC Interpreter, Eltron® EPL2®
Drivers and software	Free-of-charge from website, including support for various platforms
Flash (Non-Volatile Memory)	16 MB total, 4MB available for user
Size (W x D x H) and Weight	178 x 266 x 173 mm, 2.6 Kg

### **CL-E331**

### Label, Desktop

#### **Features & Benefits**

- Paper load: Hi-Lift™ mechanism and ClickClose™ closure
- Printing Speed: Fast print out 6 inches per second (150 mm per second)
- Media support: Large media capacity holds rolls up to 5 inches (127 mm)
- Hi-Open<sup>™</sup> case for vertical opening, no increase in footprint and safe closing.
- ENERGY STAR® compliant
- Small footprint



The CL-E331 has a wide opening 90° Hi-Lift™ case, and uses full size, 300m ribbons with standard 1 inch cores.

## **CITIZEN**

Model	CL-E331
Cutter	Guillotine type, factory installable
Warranty	2 years manufacturer's warranty or 100 Kms on printer. 6 months or 50 Kms in TT mode or 30 Kms in DT mode on printhead
<b>EMC</b> and safety standards	CE, TUV, UL, FCC, VCCI

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

### CL-E331

Label, Desktop